

HANDLING INFORMATION FOR HYDROSIZE[®] HP3-02 High Performance Waterborne Dispersion

Processing

Hydrosize[®] HP3-02 contains 8% butyl cellosolve. This solvent has a boiling point of 175°C and must be dried at a temperature high enough to remove this solvent.

Cleaning

Do not allow the solution to dry on equipment! Rinse apparatus immediately with water. If the solution dries, then it becomes more difficult to clean. If this is the case, use warm/hot water, a caustic solution, or 1-methyl-2-pyrrolidone (NMP).

Storage

Hydrosize[®] HP3-02 should be stored in tightly closed containers to prevent evaporation of water and contamination. It is recommended that storage temperatures be maintained 5°C to 20°C. Do not allow product to freeze. If a refrigerated storage area is not available, then store in a place as cool as possible and away from direct sunlight or heat source.

Health and Safety Information

Appropriate literature has been assembled which provides information pertaining to the health and safety concerns that must be observed when handling Hydrosize[®] HP3-02. Before working with any product, you must read and become familiar with the available information concerning its hazards, proper use, and handling. This cannot be overemphasized. Further information may be obtained by contacting Hydrosize[®] Technologies.

The conditions of your use and application of our products, technical assistance and information (whether verbal, written or by way of production evaluations), including any suggested formulations and recommendations, are beyond our control. Therefore it is imperative that you test our products, technical assistance and information to determine to your own satisfaction whether they are suitable for your intended uses and applications. This application-specific analysis at least must include testing to determine suitability from a technical as well as health, safety, and environmental standpoint. Such testing has not necessarily been done at Hydrosize[®] Technologies. All information is given without warranty or guarantee. It is expressly understood and agreed that customer assumes and hereby expressly releases Hydrosize[®] Technologies from all liability, in tort, contract or otherwise, incurred in connection with the use of our products, technical assistance and information. Any statement or recommendation not contained herein is unauthorized and shall not bind Hydrosize[®] Technologies. Nothing herein shall be construed as a recommendation to use any product in conflict with patents covering any material or its use. No license is implied or in fact granted under the claims of any patent.